



## ISODEC 2500

### THERMAL INSULATED DUCTING

The **ISODEC 2500** series consists of an aluminium laminate inner duct, thermally insulated with a glass wool layer and provided with an aluminium laminated outer duct. The thermal insulation is suitable for preventing condensation and minimizing heat loss and loss of cold.

#### APPLICATION

- Steam return lines
- Insulation in ventilation and air supply systems
- Air conditioning systems
- Thermic insulation in order to prevent heat loss or loss of cold
- Preventing of condensation in ventilation systems


#### SPECIFICATIONS

Article code:	DIY{Ø}
Temperature range:	
Inner duct:	-30 °C to 250 °C
Outer duct:	-30 °C to 250 °C
Operating pressure:	up to +3000 Pa
Operating air velocity:	max. 30 m/s
Min. bending radius:	0.58 x Ø + 25mm
Standard diameter range:	82 – 254 mm Bigger diameters in 50mm insulation
Standard length:	6 mtr

#### CONSTRUCTION

Inner duct:	Alu/poly laminate
Glass wool blanket:	25mm, 16kg/m³
Outer duct:	Alu/poly laminate
R-value glass wool:	0.65 m² K/W (ASTM C177-76)
Appearance:	Aluminium

#### CLASSIFICATIONS

EU (EN 13501-1):	A2-s1,d0
UK (BS476):	Part 6, 7 and 20
FR (NF):	M0/M0
Marine certified MED	


**Regulation or protocol**  
French VOC Regulation

#### Conclusion



**Version of regulation or protocol**  
Regulation of March and May 2011  
(DEVL1101903D and DEVL1104875A)

#### PRESSURE LOSS (STRAIGHT DUCT)



The **ISODEC 2500** fulfills all the requirements and are classified as specified within EN 13180:  
*Ventilation for buildings – Ductwork - Dimensions and mechanical requirements for flexible ducts.*

The **ISODEC 2500** is also available, on request, with a 50 mm glass wool layer, the article number is: DIY50{Ø}  
R-value glass wool: 1.3 (50 mm) m² K/W (ASTM C177-76). Diameter range: 082mm upto 508mm

#### Reach/RoHs Compliant

Directive 2011/65/EU RoHS

Phthalates according to 1907/2006/EC REACH

Test result: Pass - The test items meets the requirements of the test specification



#### LIABILITY:

The information contained in this brochure was current on the publication date. DEC INTERNATIONAL reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact DEC INTERNATIONAL checking for any changes in materials and/or information after this brochure was published.

#### PLEASE NOTICE:

The consultant is responsible for the actual installation and mounting of the product. The mentioned values with respect to temperatures are not appropriate to be used to determine the physical properties. These properties are also dependent on humidity and the temperature of the air inside and outside of the H.V.A.C. system.

#### TRADEMARKS:

ISODEC, the DEC logo and DEC International are trademarks, or registered trademarks of Dutch Environment Corporation BV in the Netherlands and/or other countries.

#### RESTRICTIONS:

The ISODEC ducts are not suitable for discharging combustion products from open fireplaces and oil-fired boilers. Neither are the ISODEC ducts suitable for transporting air with a high concentration of acid and base.

